

IN THE CLAIMS

1. (Currently Amended) An arrangement for connecting one end of a rod to a headed pin to enable establishing a driving engagement of connection between said pin with and said rod, including:

a housing defining a pin receiving cavity with retention features around said cavity adapted to engage a partially spherical headed portion of engaging said headed pin so as to be retained therein;

a soft elastomeric isolator ~~interposed between said housing and~~ fit to said one end of said rod to substantially enclose the same;

said housing comprised of two pieces assembled and affixed together, each piece having an isolator engaging portion generally opposing the isolator engaging portion of the other piece fit together and configured to engage and enclose said vibration isolator to create an interference fit between said housing and said isolator and also said one end of said rod, when said two pieces are fixed joined together in engagement with said isolator to form said housing.

2. (Currently Amended) The arrangement according to claim 1 wherein said housing pieces are fixed together by snap fit prongs on one housing piece received in respective receptacles on the other housing piece.

3. (Currently Amended) The arrangement according to claim 2 wherein said housing pieces are ~~molded as one part, said housing pieces~~ connected together with an integral

hinge allowing said housing pieces to be swung together into abutment with each other to assemble the same, and to be fit over and in engagement with said isolator.

4. (Currently Amended) The arrangement according to claim 3 wherein said housing pieces each have a recess defined therein, said recesses together forming ~~a~~ an isolator receiving cavity when said housing pieces are assembled abutting each other enclosing and engaging said isolator.

5. (Currently Amended) The arrangement according to claim 4 wherein said one end of said rod has a groove formed therein, and said isolator has a portion fit into said groove, said isolator having ~~a~~ an aligned outer groove formed therein, and said housing pieces each ~~having a portion~~ portions fit into said isolator groove when assembled together over said isolator.

6. (Currently Amended) The arrangement according to claim 5 wherein said ~~vibration~~ isolator has ~~a thickness of~~ portions subjected to compression of a thickness on the order of one millimeter.

7. (Currently Amended) The arrangement according to claim 1 wherein said isolator is molded over said rod one end.

8. (Currently Amended) The arrangement according to claim 1 wherein said housing pieces are ~~molded~~ made of ~~from~~ a hard plastic.

9. (Currently Amended) The arrangement according to claim 4 wherein said housing piece isolator receiving cavity has ~~an~~ said interference fit with said isolator when said housing pieces are assembled.

10. (Currently Amended) The arrangement according to claim 1 wherein said retention features comprise a prong on each housing piece projecting into said pin receiving cavity and being radially deflectable to be able to receive a said headed portion on said pin and allow passage of said headed portion on said pin past said prongs thereby, and engaging said ~~head~~ headed portion of said pin after passage thereof past said prongs.

11. (Currently Amended) The arrangement according to claim 9 wherein said prongs are each formed with an axially extending wall radially spaced from ~~said~~ a core portion of each of said housing pieces, and also having a lip projecting inwardly from said wall having a sloping under surface engaged by said ~~head~~ headed ~~on~~ portion of said pin to cause said radial deflection of said associated prong, and a blunt flat surface on each of said prongs engaging said ~~head~~ headed portion after said ~~pin~~ headed headed portion has been inserted past said prongs to retain said pin in said cavity.

12. (Currently Amended) The arrangement according to claim 1 wherein a web is formed on each housing piece extending over said pin receiving cavity on one side to prevent insertion of said pin from said one side.

13. (Withdrawn) A method of constructing a driving connection between one end of a rod and a headed pin, comprising the steps of:

molding two hard plastic housing pieces each formed with two generally semicircular recesses, each housing piece able to be fit together to form a pin receiving cavity and an isolator receiving cavity;

assembling said housing pieces to form said pin receiving cavity configured to receive said headed pin;

forming pin retention features on said housing pieces extending within said pin receiving cavity so as to be able to engage said headed pin upon insertion therein to retain the same;

disposing a soft elastomeric isolator over said one end of said rod; and,

enclosing said isolator with said housing pieces upon assembling said housing pieces together by enclosing said isolator in said isolator receiving cavity upon assembling said housing pieces together.

14. (Withdrawn) The method according to claim 13 wherein said step of assembling said housing pieces includes the step of snap fitting said housing pieces together using integrally formed engaging features on said housing pieces.

15. (Withdrawn) The method according to claim 14 further including the step of snap fitting said housing pieces together extending over said isolator on said rod.

16. (Withdrawn) The method according to claim 15 further including the step of molding said isolator over said one end of said rod prior to assembling said housing pieces to be fit over said isolator.

17. (Withdrawn) The method according to claim 13 further including the steps of molding said housing pieces together connected by an integral hinge allowing said housing pieces to be swung into abutment with each other with said recesses forming said cavities.

18. (Withdrawn) The method according to claim 16 wherein in said step of molding said isolator to said one end of said rod, said isolator is formed with a thin wall on the order of one millimeter in thickness.

19. (Withdrawn) The method according to claim 13 wherein said step of forming retention features comprises the step of molding an integral prong in each of said hard plastic housing pieces extending radially inward into an associated recess configured so that after said housing pieces are assembled together, they may engage a head portion of said pin upon insertion thereof and be deflected radially outward thereby to allow passage of said head portion and to thereafter engage said head portion to retain the same in said cavity.

20. (Withdrawn) The method according to claim 19 wherein said prong molding step includes forming a sloping under surface on said prongs to aid in producing radial outward deflection by passage of said pin head portion, and a flat surface on the end thereof

FROM :

FAX NO. :2486446530

Nov. 30 2005 02:26PM P7

engaging said pin head portion to resist extraction whereby a much greater force is required for extraction than for insertion of said pin.